

# HASCO FLOOR COATINGS





## TABLE OF CONTENTS

---

Cover	1
Table Of Content	3
Mission Statement	4
Hasco Road Marking Paint	5
Hasco Epoxy Floor Coatings	6
Hasco Acrylic Floor Coatings & Sealants	7
Hasco Masonry & Concrete Coatings	8
Product Information & Application Table	9
Hasco Color Palette	10
Adherence Table	11
Contact Information	12

HASCO

# MISSION STATEMENT

To provide our customers with quality products, excellent customer service, consultation & training



## Hasco Road Marking Paint

Hasco Road Marking paint is based on combination modified acrylic resins, designed specifically where high wear-resistance is imperative on asphalt and concrete surfaces. Hasco Road Marking is suitable for use in high traffic areas in both cold and hot climates, providing a wear-resistant, vibrant, durable surface, with a low dirt pick up property as an added feature.

Hasco Road Marking paint offers a durable solution for roads, highways, airport runways as well as race tracks.

Available as standard colors in white, black, yellow, red and blue.

- Hasco Road Marking – One component modified resins for road marking.
- Hasco Hiseal 80 – Fuel resistant elastomeric joint sealer.



Queen Alia International Airport

## Hasco Epoxy Floor Coatings

Hasco epoxy flooring solutions are suitable when a high abrasion, high impact resistant and high chemical resistant coating is required. Hasco's line of high build 100% solid Epoxy floor coatings provide a self-leveling surface with high adhesion, flexibility and durability.

Ease of application is not compromised allowing applicators to achieve better productivity.

Hasco provides a diverse epoxy floor coatings line, from crack and joint fillers, brush-able and spray-able epoxies to self-leveling solvent free coatings.

- EpoxySeal 50 - Transparent Epoxy sealer.
- Epoxy SF 260 - Epoxy Self-Leveling solvent free.
- Hasco Chemodur SF - Epoxy Roller Coat.
- Epoxy Crack Filler 100 - Crack and hole concrete filler.



Hasco Chemodur SF - Garage Private Residence



Epoxy SF 260 - Rafidi Printing Press



6 Epoxy SF 260 - ThyssenKrupp Jordan



Epoxy Crack Filler 100



Epoxy SF 260 - Kan Zaman Kitchen

## Hasco Acrylic Floor Coatings & Sealants

Hasco's line of one component acrylic coatings and sealants offers a versatile easy to apply flooring solution suitable for application on concrete and metal floors in both clear and pigmented options. Hasco one component acrylic coatings offers contractors a flexible light stable solution applicable under external conditions by brush or roller. These easy to use coatings offer weathering resistance, anti-dusting properties, and moisture sealing of substrates while allowing for easy repair.

- AcrySeal 60 - One component MMA clear concrete sealant, provides excellent non yellowing protection for interior and exterior concrete. AcrySeal 60 protects concrete from dusting and degradation. Most suitable as a sealant over concrete and stamped concrete surfaces.
- AcryFloor 100 - One component Styrene Acrylic coating especially suited for exterior courts, parking lots and play grounds, where high abrasion resistance, weather stability and mechanical resistance are required.



AcrySeal 60 - Factory Floor



AcryFloor 100 - Private Tennis Court

- Hasco HydroUrethane 550 - Two component Water based Aliphatic Polyurethane floor coating, specially designed for areas of heavy traffic and exterior parking lots where epoxy coatings are not suitable. HydroUrethane 550 provides excellent mechanical, weather and chemical resistance.



Hasco HydroUrethane 550 - Private Offices/Qobain

## Hasco Masonry & Concrete Coatings

Hasco provides unique coatings for most building materials from masonry to gypsum board and cement.


- Hascoton – Vinyl Acrylic self-priming topcoat is suitable for most building material and cement substrates. Hascoton provides a breathable exterior grade topcoat suitable for marine environments as well as damp interior spaces. Hascoton has anti-fungal properties to provide a long-life coating solution even in wet climates.
- Hasco SilcoSeal – Clear silicon coating based on a combination Silane and Siloxane resin that bonds with most building material to provide a water and dirt repellent sealed surface.
- Liquiclean 25 – Water-based all purpose cleaner and degreaser. A substrate safe, aluminum safe, food safe and biodegradable cleaner, that provides superior foaming action to gently lift dirt and brighten surfaces. Environmentally and health friendly.
- Marbawax - Wax/Resin compound for ageing marble, granite and various types of stone . Helps restore gloss and prevent water absorption of aged marble and granite.



8 Hasco SilcoSeal - Private Residence



Marbawax - Marble Floor/Hotel



Hascoton - Al-Baraka Mall




## PRODUCT INFORMATION & APPLICATION TABLE


Product	Hardener	Thinner	Mixing Ratio	Application	Miscellaneous
AcryFloor 100	N/A - 1K	PU-66	Thinner 20-50%	Exterior sports courts, playgrounds and concrete substrates	Pigmented protective & decorative coating for vertical and horizontal surfaces
AcrySeal 60	N/A - 1K	PU-66	N/A	Acrylic non yellowing concrete and stamp concrete sealer	Non yellowing glossy sealer for concrete
Epoxy Seal 50	Hardener 4N	N/A	Hardener 40% by volume	Epoxy concrete sealer	Impregnating, adhesion promoting Sealer/ Dust prevention
Epoxy SF 260	Hardener 4N	N/A	Hardener 50% by volume	Self-Leveling epoxy coat	Self leveling - Suitable for heavy traffic and heavy loads - high chemical resistance
Chemodur SF	Hardener 4N	PU-11	Thinner 0-5% Hardener 40% by Volume	Roller Coat concrete coating	Flexible, impact and chemical resistant coating
Epoxy Crack Filler 100	Hardener 4N	N/A	Hardener 40% by volume	Crack & hole filler	Silica sand added for extra strength
Hasco Hiseal 80	N/A	N/A	N/A	Fuel resistant elastomeric joint sealant	Airfield certified sealer
Hasco Road Marking	N/A - 1K	PU-22	Thin between 5-25% by volume	Cold apply, easy to apply road marking paint	Available in reflective & non reflective versions
Hasco SilcoSeal	N/A	N/A	Ready to use	Water & dirt repellent	Masonry sealer
Hascoton	N/A - 1K	PU-66	Thin up to 50%	Interior & exterior coating	Weather resistant, alkali resistant non saponifiable coating
Hasco Marbawax	N/A	N/A	Ready to use	Wax for marble	Ageing and wet look effect for marble
Hasco HydroUrethane 550	Hardener AX	Water	Hardener 10% by volume	Water based environmentally friendly floor coating	Polyurethane with excellent weather, chemical, mechanical resistance. Water resistant, and anti slip (non yellowing)
Hasco LiquiClean 25	N/A	Water	Mix with 4 to 15 parts of water	Versatile all purpose cleaner	Environmentally friendly, food safe, biodegradable, aluminum safe

# Hasco Color Palette


Printed Colors may vary from actual paint color



HS 013




HS 021



HS 031




HS 041



HS 051



HS 061



HS 071



HS 014




HS 022



HS 032



HS 042



HS 052



HS 062



HS 072



HS 015



HS 023



HS 033



HS 043



HS 053



HS 063



HS 073



HS 016



HS 024



HS 034



HS 044



HS 054



HS 064



HS 074



HS 017



HS 025



HS 035



HS 045



HS 055



HS 065



HS 075



HS 018



HS 026



HS 036



HS 046



HS 056



HS 066



HS 076



# PRODUCT ADHERENCE TABLE

Hasco HiSeal 80	ASTM D3569-85. ASTM D3406-85. BS2499 1973 Types A1 and B1	
Hasco Road Marking	I.S. EN 1436:2007 Road Marking Materials – Road Marking Performance for Road users	
	ASTM E2176-01 Standard Test Method for Measuring the Coefficient of Retroreflected Luminance	
	Skid test, over 63 S.R.T (D.S.I.R)	
Hascoton/Chemolac	Adhesion/resistance to green concrete; NEN 5337 - after 7 days - good	
	Flexibility; good, after 5 hours aging at 80 degrees Celsius start of cracking at Erichsen > 6mm	
	Impact resistance, ASTM D2794-69, ball diam 20mm, resistance in kg/cm > 200	
	Film hardness; NEN standard for wall coatings. Sufficient after 1 day, determined with Persoz hardness tester	
	Liquid vapour permeability; Two coat system on concrete tile, show hascoton as impermeable to liquid water	
	Water Vapour; BS 2972 Section 12. Two coat system mean result g/m2/day 2,87 (mean results under 13 considered barriers under normal conditions)	
	Chemical resistance; resistant to most thinned alkali and inorganic acids, mineral oils, water and seawater. Not resistant against organic acids.	
Chemodur (Roller Coat Epoxy)	Hardness, shore D ASTM D 2240	65-80
	Tensile Strength ASTM D 638	7 days cure @ 70-75F 4000
	Elongation % @ ASTM D 638	5-10 / 7 days cure @ 70-75F
	Compressive Strength, ASTM D 575	Psi 10,000+
	Impact strength, ASTM D 4226	in.-lbs. falling ball method 10+
	Low Temperature Flexibility ASTM D 3111 (10 mil thickness)	360 Bend 1/4" mandrel @ -15F
Epoxy SF 260 (Self Leveling Epoxy)	Hardness (Shore D) ASTM D-2240	85
	Tensile Strength (psi) ASTM D-638	7000 – 7500 Psi
	Flexural Strength (psi) ASTM D-790	17,900 Psi
	Elongation (%) ASTM D-638	4.5%
	HDT ASTM D-648-264	120°F
	Compressive Strength (psi) ASTM D-695	10,000+ Psi
	Water Absorption, gain in 24 hrs (%) ASTM D-570	<1%

# HASCO

## The New Standard of Coating Quality

### CONTACT INFORMATION

---



E-mail: [sales@sroujiholding.com](mailto:sales@sroujiholding.com)

#### ADDRESS

11 Sina'a Street  
Wadi Essyr  
Amman 11810  
Jordan

#### JORDAN

Tel. + 962 6 5855375/6  
FAX + 962 6 5855380

#### BULGARIA

Tel. + 359 2 9887060  
Fax + 359 2 9863016  
Mob. + 359 888 802 523

---

FOR MORE INFORMATION VISIT OUR WEBSITE [WWW.SROUJIHOLDING.COM](http://WWW.SROUJIHOLDING.COM)